

Belt Wrap Capstan Models & Specs

BELT WRAP CAPSTANS					
Model Numbers	Description	Sheave Diameter	Groove Width	Maximum Wire Diameter	Maximum Line Speed
CBW-16	16" General Purpose	16"	1"	1/4"	2500 fpm
		406 mm	25 mm	6 mm	760 mpm
CBW-16D	16" General Purpose with 4 speed transmission	16"	1"	1/4"	2500 fpm
		406 mm	25 mm	6 mm	760 mpm
FO-CBW-16	16" Fiber Optic Belt Wrap Capstan	16"	1"	Tight Buffer	2500 fpm
		406 mm	25 mm	6 mm	760 mpm
CBW-24	24" General Purpose	24"	1"	3/8"	2500 fpm
		610 mm	25 mm	9.5 mm	760 mpm
CBW-24D	24" General Purpose with 4 speed transmission	24"	1"	3/8"	2500 fpm
		610 mm	25 mm	9.5 mm	760 mpm
FO-CBW-24	24" Fiber Optic Belt Wrap Capstan	24"	1"	Loose Tube	2500 fpm
		610 mm	25 mm	9.5 mm	760 mpm
CBW-36	36" General Purpose with 4 speed transmission	36"	2"	1"	1500 fpm
		914 mm	50 mm	25 mm	450 mpm
CBW-36D	36" General Purpose with 4 speed transmission	36"	2"	1"	1500 fpm
		914 mm	50 mm	25 mm	450 mpm
CBW-48D	48" General Purpose with 4 speed transmission	48"		2 1/2"	1000 fpm
		1219 mm		63 mm	300 mpm