



Single Reel Payoff



Features

- Pushbutton or optional touchscreen Controls
- Drag or driven models
- No timing belts or sheaves
- Optional in-line 4-speed transmission
- Compact footprint
- Easy to load
- Emergency stop limit switch
- AC vector drive
- PLC Control
- Wide reel range
- Heavy lifting capacity
- Capable for use with accumulator filling programs

PAYOFFS

Model Numbers	Description	Reel Diameter Range	Reel Width Range	Lifting Capacity	Maximum Speed
PO-36-HD	36" Single Reel Payoff - Drag	18" - 39 3/8"	11" - 24"	4,000 lbs	2,000 fpm
		460mm - 1000mm	280mm - 610mm	1800 kg	600 mpm
PO-36-HD-M	36" Single Reel Payoff - Motorized	18" - 39 3/8"	11" - 24"	4,000 lbs	2,000 fpm
		460mm - 1000mm	280mm - 610mm	1800 kg	600 mpm
PO-36-MB	36" Single Reel Strander Payoff with integral dancer	18" - 39 3/8"	11" - 24"	4,000 lbs	1,000 fpm
		460mm - 1000mm	280mm - 610mm	1800 kg	300 mpm
PO-60-HD	60" Single Reel Payoff - Drag	24" - 60"	18" - 38"	6,000 lbs	1,000 fpm
		610mm - 1520mm	460mm - 960mm	2700 kg	300 mpm
PO-60-HD-M	60" Single Reel Payoff - Motorized	24" - 60"	18" - 38"	6,000 lbs	1,000 fpm
		610mm - 1520mm	460mm - 960mm	2700 kg	300 mpm
PO-72-HD-M	72" Single Reel Payoff - Motorized	30" - 72"	18" - 38"	10,000 lbs	1,000 fpm
		762mm - 1830mm	460mm - 960mm	4500 kg	300 mpm